Lightology

lightology.com
866-954-4489
11-08-26

Project:

Company:

Location: Fixture Type:

SPEC #: **WAC998506**

Approved On: Approved By:

Lotos Round Color-Select Downlight Trim with Remote Driver


By WAC Lighting

Description

The Lotos 4 or 6 Inch Round Downlight Trim with Remote Driver features a wafer thin profile with included driver, a translucent slim acrylic diffuser, and frosted TIR lens. A color temperature switch on the driver allows the color temperature to be selected from 2700K, 3000K, 3500K, 4000K, or 5000K prior to installation. The Fire-Rated version is ASTM E119 and UL 263 tested and certified for 2 hours to reduce the spread of fires and maintain ceiling integrity. TRIAC and ELV dimming. Optional mounting plate sold separately.Note: Fire rated option available in White finish only. Minimum plenum space required for fire rated is 4.5 inch.



Shown in white / frosted



Specifications

REFLECTOR/BAFFLE COLOR	Frosted
BODY FINISH	White
WATTAGE	8W
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 1"H
INTEGRATED LED MODULE	1 x LED/8W/120-277V LED

Technical Information

APERTURE SIZE	4.000"
APERTURE SHAPE	Round
HOUSING HEIGHT	1"
HOUSING TYPE	Remodel IC Airtight
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
COLOR RENDERING	90 CRI
LAMP COLOR	CCT Select
LUMENS/WATT	90.63
LUMINOUS FLUX	725 lumens

CLICK TO VIEW PRODUCT

Notes: